

SAFARE' CUSTOM CAMPERS



OWNERS MANUAL

A WORD TO SAFARE OWNERS...

This manual has been prepared to acquaint you with the operation of your Safare Custom Camper, and to provide important operating information. We urge you to read this publication carefully and follow the recommendations to help assure the most enjoyable and troublefree operation of your vehicle.

STOVE:

The two burner stove is designed for safety and ease while cooking. The butane tank is located on the underside on the van, directly behind the front right wheel. The middle valve (Figure #1) on the tank will open and close the butane supply with arrows showing the direction for butane flow. To the rear of the flow valve is the fill valve. Open the flow valve completely, turn stove burner on, and ignite with a match.





ELECTRIC REFRIGERATOR:

The refrigerator will run on either the van's 12 volt dual batteries Or 100 volt hook-up. Inside the refrigerator, in top right corner, is a dial with 1-5 settings for cooling. For normal cooling, it is recommended to set the dial on 3.

For cooling with 110 volt, a 20' extension cord is located behind the driver's seat. Remove the cord and connect to the hook-up (Figure #2) Located outside on driver's side. Connect to any 110 volt source. When ever the refrigerator is being run on 110 volt, the plug on the refrigerator cabinet (Figure #3) must be connected.

The meter (Figure #4) located on the refrigerator cabinet registers voltage level in battery while the refrigerator is in operation. The battery charger is located under the left dinette seat and will charge the auxiliary battery when connected to 110 volt source. The reset button on the main circuit breaker box is located under the left side dinette seat.

SINK AND WATER CABINET:

Your hand pump may be used for a smooth steady flow of water by simply pulling the handle forward. By leaving the handle in the down position, finger rip motion delivers water from any city water hookup. For a flow of water without an electric pump, simply rock the pump handle back and forth.

Your twelve gallon holding tank fill (Figure -5) is located outside of the van parallel to the sink. This fill is designed to padlock for safety. Directly below the fill and under the van, is the petcock drain for draining the water tank. Under the van, and to the rear of the petcock drain, is the opening for any water in the sink, with an eleven gallon holding tank and a 3" dump valve for ease. This drain is designed with a closing cap and conforms to the State Law regulating drainage. This unit is designed to drain all grey waste water. A hose may be attached for draining into a container or hookup.

LIGHTING AND ROOF VENT:

Inside the van is a double fluorescent light and vent for your convenience and comfort. To operate the light and vent, the accessory switch on the front dash must be pulled on. Simply set the lighting and ventilation for your needs.



OPTIONAL FRONT HAMMOCK:

Located behind both front seats are brackets. Snap in firmly both ends of hammock posts into brackets. Simply pull the hammock directly out and attach nylon hooks to the front catches. This hammock is designed to support up to 135 pounds.

TOP HAMMOCK:

In the upper part of the van, front and back, are the brackets for holding the hammock. The back bracket can be permanently attached. The front bracket is removable for safety and is stored in the cupboard above the side windows. Simply slide the bottom spacer through the hole, place the top spacer above, attach nut and tighten. To open the hammock, pull inner post straight out, and snap into brackets. To replace the hammock in storing position, snap the post out of brackets and roll back into storing position above door. This hammock is six feet long and is designed to support 175 pounds.

MAIN DOUBLE BED:

This bed is designed specifically for the sleeping comfort of two adults. Remove the dinette table by lifting it to a 45 degree angle, push the leg latch to fold leg up to the table in a lock position, and pull the table off the support bracket. Place the table between the dinette seats on the lower supporting bracket. Place the back cushions of the dinette seats over the table. This arrangement may be used for a small day bed for children or for seating of passengers while traveling. On either side of dinette seats are sliding bolts. Pull these open and pull the bed forward with the two handles on the top of the bed. Completely open, the bed measures four feet by over six feet to insure comfort and ease while sleeping. To place the bed into storing position, simply push the bed back, and snap the bolts into place. Place the dinette cushions into position and snap the dinette table into its top supporting bracket. The table leg will automatically go into place by pressing the leg latch. This bed can be opened and closed with full bedding and pillows.

OPTIONAL SLIDE OUT BED:

This bed is stored above your large bed at the rear of the camper. Remove the three cushions and the locking pin in the centre of the bed. grasp the handles on the front of the bed frame and pull completely out. The three sections are built on rollers and will fall into place. Place your cushions on top of the frame and you have a bed for sleeping comfort that is four feet by six feet and will support up to 300 pounds. To replace the bed, remove the cushions, push the first board onto the middle board and continue pushing both sections onto the stationary board. Because of roller bearings, this should be one smooth motion. Check the alignment of the boards with the bed board guides at this point, push into locking position and replace pin.



POP TOP CONVERSION:

To open your Pop Top, unsnap the three flaps completely. Unhook the four T handles, grasp the two handles in the roof and push up. Your Pop-Top will then automatically lock into place. After the Pop Top section is lifted, the fold out section may be pulled out for use of your 6' bed.

To close your Pop Top, fold up the bed, grasp the two handles in the roof and firmly pull down halfway. At this point, pull the canvas into the van to avoid the roof scissor mechanisms. Keep the four T handles inward. Continue to firmly pull the Pop Top down. Fold the canvas so that the flaps will cover. Lock the four T handles and resnap flaps.

Your purchase of a Safare Custom Camper is greatly appreciated by our dealer and Safare Custom Campers. It is our sincere desire to assist you in any way possible to assure your complete satisfaction with your vehicle.

VOLKSWAGEN VAN CONVERSION

SAFARE' CUSTOM CAMPERS

15343 Allen Avenue,
Paramount,
Calif. 90723 (213) 634-0451